.ECHO

Power range 3-13 kVA

Generating sets 3000-3600 RPM - 50/60Hz - 400-230V/480-277V

ELCOS
POWER GENERATORS

Powered by
iGX Engine

Emergency response
Pronto intervento

Designed to be portable
Portatile

For Domestic use
Per uso domestico

Generating sets designed to offer portable power solutions

The ECHO series generators offer a wide range of uses and engine brands

Gruppi elettrogeni realizzati per offrire soluzioni energetiche portatili

La serie ECHO offre un'ampia gamma di utilizzi e motori

www.elcos.net

GE.ECHO

Power Generators 3 - 13 kVA

3000-3600 RPM DIESEL
50/60HZ - 400-230V/480-277V

	1P 230V		3P 400V												
	KVA	KW	KVA	KW	AMPERE	BRAND	CODE	DISPLACEMENT	CYLINDERS	TANK lt	LOAD@75%-h	NOISE @ 7 m	DIMENSIONS - L x W x H	WEIGHT kg	PANEL
Gasoline - *Benzina*	**Snatch start up** - *Avviamento a strappo*														
GE ECHO 035 H BM AS	3,5	2,8	-	-	12	Honda	GX 160	163	1L	3	3,3	69	62 x 44 x 54	47	1
GE ECHO 048 H BM AS	4,8	3,8	-	-	17	Honda	GX 270	270	1L	5	4,2	69	76 x 52 x 62	71	1
GE ECHO 065 H BM AS	6,5	5,2	-	-	23	Honda	GX 390	389	1L	6	3,5	70	76 x 52 x 62	91	2
GE ECHO 070 H BT AS	4*	3,2	7	5,6	10	Honda	GX 390	389	1L	6	3,3	69	76 x 52 x 62	91	3
Gasoline - *Benzina*	**Electric start up** - *Avviamento elettrico*														
GE iECHO 048 H BM AE	4,8	3,8	-	-	17	Honda	iGX 270	270	1L	5	4,2	69	76 x 52 x 62	85	1
GE iECHO 065 H BM AE	6,5	5,2	-	-	23	Honda	iGX 390	389	1L	6	3,8	70	76 x 52 x 62	105	2
GE iECHO 070 H BT AE	4 *	3,2	7	5,6	10	Honda	iGX 390	389	1L	6	3,5	72	76 x 52 x 62	105	3
GE ECHO 110 H BM AE	11	8,8	-	-	38	Honda	GX 390	628	2V	13	4,1	70	78 x 52 x 75	123	2
GE ECHO 110 H BT AE	7*	5,6	11	8,8	16	Honda	GX 630	628	2V	13	4,1	72	78 x 52 x 75	130	3
Diesel - *Diesel*	**Electric start up** - *Avviamento elettrico*														
GE ECHO 045 Y DM AE	4,5	3,6	-	-	16	Yanmar	L 70	320	1L	4	4,0	74	76 x 52 x 69	100	1
GE ECHO 065 Y DM AE	6,5	5,2	-	-	23	Yanmar	L 100	435	1L	6	4,3	74	76 x 52 x 69	120	2
GE ECHO 070 Y DT AE	4*	3,2	7	5,6	10	Yanmar	L 100	435	1L	6	4,0	74	76 x 52 x 69	122	3
GE ECHO 110 K DM AE	10	8	-	-	35	Kohler	25LD330	654	2L	13	7,2	80	85 x 52 x 75	145	2
GE ECHO 110 K DT AE	6,5*	5,2	10	8	16	Kohler	25LD330	654	2L	13	7,2	80	85 x 52 x 75	145	3
GE ECHO 130 K DT AE	8,5*	6,8	13	10,4	19	Kohler	25LD425	851	2L	13	4,5	80	85 x 52 x 75	150	3

* Not to be taken simultaneously with the three-phase power - *Non prelevabile contamporaneamente alla potenza trifase*

GE ECHO 035 H

GE ECHO 065 Y

GE iECHO 048 H

GE ECHO 048 H

GE ECHO 110 H

GE ECHO 130 K

Equipment - *Dotazioni*

Low oil shutdown system
Spegnimento per mancanza olio

Heat guards
Protezione parti calde

Tank protected against impacts
Protezione antiurto serbatoio

Tube-shaped frame
Telaio tubolare

Battery - *Batteria**
*Only AE models - *Solo modelli AE*

Snatch start up
Avviamento Autoavvolgente

Auto choke system - ***Starter automatico***
High Performance - ***Elevate prestazioni***

On board Control panels *Quadri a bordo*

Type -*Tipo* **1**

1 Socket - *Presa* **Schuko 16A 230V**
1 Socket - *Presa* **CEE 16A 2P + T 230V**
Voltmeter - *Voltmetro*
Circuit breaker - *Disgiuntore*
Hour counter - *Contaore*

Type -*Tipo* **2**

1 Socket - *Presa* **CEE16A 2P + T 230V**
1 Socket - *Presa* **CEE 32 A 2P + T 230V**
Voltmeter - *Voltmetro*
Magneto-thermal switch - *Int. magnetotermico*
Hour counter - *Contaore*

Type -*Tipo* **3**

1 Socket - *Presa* **CEE 16A 2P + T 230V**
1 Socket - *Presa* **CEE 32A 3P+N+T 400V**
Voltmeter - *Voltmetro*
Magneto-thermal - *Int. magnetotermico*
Hour counter - *Contaore*

ELCOS
POWER GENERATORS

ELCOS SRL
Strada Statale 234 Km 58.250 -
26023 Grumello Cremonese CR - Italy
tel +39 0372 72330 - fax +39 0372 7233220
PI 01084730199
info@elcos.net - elcos@pec.elcos.net

www.elcos.net